

COMPREHENSIVE SERVICES

We offer competitive repair and calibration services, as well as easily accessible documentation and free downloadable resources.

SELL YOUR SURPLUS

We buy new, used, decommissioned, and surplus parts from every NI series. We work out the best solution to suit your individual needs.

 Sell For Cash  Get Credit  Receive a Trade-In Deal

OBSOLETE NI HARDWARE IN STOCK & READY TO SHIP

We stock **New**, **New Surplus**, **Refurbished**, and **Reconditioned** NI Hardware.



Bridging the gap between the manufacturer and your legacy test system.

 1-800-915-6216

 www.apexwaves.com

 sales@apexwaves.com

All trademarks, brands, and brand names are the property of their respective owners.

Request a Quote

 **CLICK HERE**

PCI-6111

Board Assembly Part Number(s)

Part Number	Description
777530-01 and all previous letter revisions	NI PCI-6111

Manufacturer: National Instruments

Volatile Memory

Type ¹	Size	Access Restrictions	Method of Clearing
Analog Input FIFO	8192 x 18-bit	Not User Accessible	Cycle Power
Analog Output FIFO	2048 x 18-bit	User has write access through API	Cycle Power
Counter Input HW	1 Sample (32-bit)	Not User Accessible	Cycle Power

Non-Volatile Memory

Type	Size	Access Restrictions	Method of Clearing
Calibration EEPROM	512k x 8-bit	Limited read/write access from the API.	Use the NI-DAQmx API
MITE EEPROM	8k x 8-bit	Not User Accessible	None Available to User
Device Config. EEPROM	440800 x 1-bit	Not User Accessible	None Available to User

Terms and Definitions

User Accessible Allows the user to directly write or modify the contents of the memory during normal instrument operation.

System Accessible Does not allow the user to access or modify the memory during normal instrument operation. However, system accessible memory may be accessed or modified by background processes. This can be something that is not deliberate by the user and can be a background driver implementation, such as storing application information in RAM to increase speed of use.

Cycle Power The process of completely removing power from the device and its components. This process includes a complete shutdown of the PC and/or chassis containing the device; a reboot is not sufficient for the completion of this process.

Volatile Memory Requires power to maintain the stored information. When power is removed from this memory, its contents are lost.

Non-Volatile Retains its contents when power is removed. This type of memory typically contains calibration or chip configuration information, such as power up states.

¹ Calibration constants that are stored in device EEPROMs include information for the device's full operating range and does not maintain any unique data for specific frequencies at which the device is used. Calibration Records do contain the date and temperature of last calibration.