
PXI-2544

Specifications

2025-07-22



Contents

PXI-2544 Specifications 3

PXI-2544 Specifications

PXI-2544 Specifications

These specifications apply to the PXI-2544 .

All specifications are subject to change without notice.



Notice The protection provided by the PXI-2544 can be impaired if it is used in a manner not described in this document.

About These Specifications

Specifications characterize the warranted performance of the instrument under the following operating conditions:

- Chassis is powered on
- Calibration adjustment cycle maintained
- 50 Ω termination connected to unused I/O front panel connectors

Typical Specifications are specifications met by the majority of the instrument under the stated operating conditions and are tested at 23 °C ambient temperature. Typical specifications are not warranted.

Nominal values (or supplemental information) describe additional information about the product that may be useful, including expected performance that is not covered under **Typical Specifications**. Nominal values are not covered by warranty.

All voltages are specified in DC, AC_{pk}, or a combination unless otherwise specified.

Clean devices and terminal blocks by brushing off light dust with a soft, nonmetallic brush. Remove other contaminants with a soft, lint-free, dampened cloth. Do not use detergent or chemical solvents. The unit must be completely dry and free from contaminants before returning to service.

PXI-2544 Pinout




Table 1. Signal Descriptions

Signal	Description
CHx	Signal connection
COM	Routing destination for all channels
TRIG IN	Trigger input connection
TRIG OUT	Trigger output connection

Related information:

- [PXI-2544 Hardware Diagram](#)
- [NI Switches Cable and Accessory Compatibility](#)

Topology

Topology	8x1 terminated multiplexer
----------	----------------------------

Input Characteristics

Minimum input frequency	10 MHz
Characteristic impedance (Z_0)	50 Ω nominal
Coupling	AC
Maximum safe DC input voltage	$\pm 8V$

Maximum Safe Continuous RF Power

Chassis power ON	+30 dBm
Chassis power OFF	+20 dBm

RF Performance Characteristics

Values in parentheses are typical.

Insertion loss

≤2.4 GHz	<4.5 dB (<3.2 dB)	
≤6 GHz	<6.3 dB (<5.2 dB)	
≤6.6 GHz	<7.2 dB (<6.0 dB)	
Insertion loss thermal coefficient		α = 3,402 ppm/°C

Use the following equation to calculate the insertion loss at a given temperature:

$$IL_T = IL_{T_0} \left(1 + \alpha (T - T_0) \right) \quad IL_T = IL_{T_0} \left(1 + \alpha (T - T_0) \right)$$

where	IL is insertion loss in dB
	T is the temperature at which the property is being measured in °C
	T ₀ is the reference temperature in °C
	α represents insertion loss temperature coefficient in ppm/°C

Table 2. PXI-2544 Flatness (Typical)

Frequency	Flatness / 200 MHz	Flatness / 1 GHz
10 MHz to 5 GHz	<0.30 dB	<0.8 dB
5 GHz to 6 GHz	<0.32 dB	<1.0 dB
6 GHz to 6.6 GHz	<0.47 dB	<1.3 dB

Voltage standing wave ratio (VSWR)	
10 MHz ≤ x ≤ 3.5 GHz	<1.9 (<1.5)

3.5 GHz < x≤6 GHz		<1.9 (<1.4)
6 GHz < x≤6.6 GHz		<2.2 (<1.6)
CH-COM isolation		
≤2.4 GHz	>77 dB (>95 dB)	
≤6 GHz	>65 dB (>77 dB)	
≤6.6 GHz	>61 dB (>72 dB)	
CH-CH isolation		
≤2.4 GHz	>77 dB (>95 dB)	
≤6 GHz	>62 dB (>82 dB)	
≤6.6 GHz	>56 dB (>76 dB)	
Typical channel-to-channel skew		<10 ps
Typical propagation delay		1100 ps
Input 1 dB compression		
Minimum	>27 dBm	

Typical	>32 dBm
---------	---------

Refer to the following figures for typical insertion loss, typical VSWR, and typical isolation, respectively.

Figure 1. Typical Insertion Loss




Figure 2. Typical VSWR





Figure 3. Typical Isolation



Linearity

Second-order harmonic distortion (Input IP2 (IIP2))

Typical IP2 (input)	>+91 dBm
---------------------	----------

**Note** Measurements are performed with single CW tones, ranging from -26 dBm to +10 dBm at the RF input. This specification is based on both experimental and calculated data.

Third-order intermodulation distortion (Input IP3 (IIP3))

Typical IP3 (input)	>+56 dBm
---------------------	----------

**Note** Measurements performed with two 10 dBm input tones = 1 MHz apart. This specification is based on both experimental and calculated data.

Dynamic Characteristics

Relay Operate Time

Typical	1 ms
Maximum	3.3 ms
Simultaneous drive limit	90 relays
Expected mechanical relay life	1×10^8 cycles
Expected electrical relay life	
≤ 30 mV, ≤ 10 mA resistive	2.5×10^6 cycles
30 V, 1 A	5×10^5 cycles
30 V, 2 A	1×10^5 cycles
60 VDC, 1 ADC resistive	1×10^5 cycles



Note Relays are field replaceable. Refer to the ***NI Switches Help*** at ni.com/manuals for more information about replacing a failed relay.

Trigger Characteristics

Input trigger	
Sources	PXI trigger lines 0 –7, front panel

Minimum pulse width	150 ns
Front panel input voltage	
Minimum	-0.5 V
V _L maximum	+0.7 V
V _H minimum	+2.0 V
Nominal	+3.3 V
Maximum	+5.5 V
Output trigger	
Destinations	PXI trigger lines 0–7, front panel
Default pulse width	2 μ s, typical
Front panel nominal voltage	3.3 V TTL, 8 mA

Physical Characteristics

Switch type	FET
Front panel connectors	

I/O	9 SMA jacks, female	
Triggers	2 SMB jacks, female	
Power requirement		
PXI		
5 V	0.1 W	
3.3 V	0.6 W	
PXI Express		
12 V	0.6 W	
3.3 V	0.9 W	
Dimensions (L × W × H)	3U, one slot, PXI/cPCI module, PXI Express compatible 21.6 cm × 2.0 cm × 13.0 cm (8.5 in. × 0.8 in. × 5.1 in.)	
Weight	538 g (19 oz)	

Environment

Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Pollution Degree	2

Indoor use only.

Operating Environment

Ambient temperature range, operating	0 °C to 55 °C
Relative humidity range, operating	10% to 90%, noncondensing

Storage Environment

Ambient temperature, storage	-40 °C to 71 °C
Relative humidity range, storage	5% to 95%, noncondensing

Shock and Vibration

Operating shock	30 g peak, half-sine, 11 ms pulse
Random vibration	- Operating: 5 Hz to 500 Hz, 0.3 g RMS - Nonoperating: 5 Hz to 500 Hz, 2.4 g RMS

Compliance and Certifications

Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



Note For safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations, certifications, and additional information, refer to ***Product Certifications and Declarations***.

Product Certifications and Declarations

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit ni.com/product-certifications, search by model number, and click the appropriate link.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Engineering a Healthy***

Planet web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国RoHS）

-  **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)