PXIe-8280 Safety, Environmental, and Regulatory Information



PXIe-8280 Safety, Environmental, and Regulatory Information

PXIe, 1-Port 50 Gigabit PXI RDMA Ethernet Interface Module

Contents

Safety, Environmental, and Regulatory Information	3
lcons	
Safety Guidelines	
EMC Guidelines	
Environmental Guidelines	
Power Requirements	
Physical Characteristics	
Export Compliance	7
Environmental Management	
Product Certifications and Declarations	
NI Services	

Safety, Environmental, and Regulatory Information

Read this document before you install, configure, operate, or maintain this product. Users are required to familiarize themselves with installation and wiring instructions in addition to requirements of all applicable codes, laws, and standards. Visit ni.com/manuals for more information about your product, including specifications, pinouts, and instructions for connecting, installing, and configuring your system.

lcons

Refer to the following descriptions for the icons marked on your product or used in this guide.

- **Notice** Take precautions to avoid data loss, loss of signal integrity, degradation of performance, or damage to the product.
- ⚠ **Caution** Take precautions to avoid injury. Consult the product documentation for cautionary statements when you see this icon printed on the product. Cautionary statements are localized into French for compliance with Canadian requirements.
- **ESD Sensitive** Take precautions to avoid damaging the product with electrostatic discharge.

Safety Guidelines



CAUTION

Observe all instructions and cautions in the user documentation. Using the product in a manner not specified can damage the product and compromise the built-in safety protection.

ATTENTION

Suivez toutes les instructions et respectez toutes les mises en garde de la documentation d'utilisation. L'utilisation du produit de toute autre façon que celle spécifiée risque de l'endommager et de compromettre la protection de sécurité intégrée.

Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

IEC 61010-1, EN 61010-1

UL 61010-1, CSA C22.2 No. 61010-1



NOTE

For safety certifications, refer to the product label or the *Product Certifications and Declarations* section.

EMC Guidelines

This product was tested and complies with the regulatory requirements and limits for electromagnetic compatibility (EMC) as stated in the product specifications. These requirements and limits are designed to provide reasonable protection against harmful interference when the product is operated in its intended operational electromagnetic environment.

This product is intended for use in commercial and light-industrial locations. However, harmful interference may occur in some installations, when the product is connected to a peripheral device or test object, or if the product is used in residential areas. To minimize interference with radio and television reception and prevent unacceptable performance degradation, install and use this product in strict accordance with the instructions in the product documentation.

Furthermore, any changes or modifications to the product not expressly approved by NI could void your authority to operate it under your local regulatory rules.

EMC Notices

Refer to the following notices for cables, accessories, and prevention measures necessary to ensure the specified EMC performance.

①

NOTICE

For EMC declarations and certifications, and additional information, refer to the *Product Certifications and Declarations* section.

①

NOTICE

Changes or modifications to the product not expressly approved by NI could void your authority to operate the product under your local regulatory rules.

①

NOTICE

Operate this product only with shielded cables and accessories unless using an optical cable.

EMC Standards

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions

AS/NZS CISPR 11: Group 1, Class A emissions



Group 1 equipment is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



In Europe, Australia, and New Zealand (per CISPR 11) Class A equipment is intended for use in non-residential locations.

Environmental Guidelines

NOTICE

This product is intended for use in indoor applications only.

(!)

NOTICE

All cabling should be strain-relieved near input connectors. Take care not to directionally bias cable connectors within input connectors when applying strain

Environmental Characteristics

0 °C to 55 °C
-40 °C to 71 °C
10% RH to 90% RH, noncondensing
5% RH to 95% RH, noncondensing
2
2,000 m
5 Hz to 500 Hz, 0.3 g RMS
5 Hz to 500 Hz, 2.4 g RMS
30 g, half-sine, 11 ms pulse

The PXIe-8280 requires a chassis with slot cooling capacity ≥58 W. Not all chassis with slot cooling capacity ≥58 W can achieve this ambient temperature range. Refer to PXI chassis specifications to determine the ambient temperature ranges your chassis can achieve.

Environmental Standards

This product meets the requirements of the following environmental standards for electrical equipment.

- IEC 60068-2-1 Cold
- IEC 60068-2-2 Dry heat
- IEC 60068-2-78 Damp heat (steady state)
- IEC 60068-2-64 Random operating vibration
- IEC 60068-2-27 Operating shock



NOTE

To verify marine approval certification for a product, refer to the product label or visit *ni.com/certification* and search for the certificate.

Power Requirements

The PXIe-8280 draws current from a combination of the 3.3 V and 12 V power rails. The maximum current drawn from each of these rails can vary depending on the cable connected to the module.

Table 1: PXIe-8280 Power Requirements

Cable Type	Power Rail	Typical	Maximum
Passive Direct Connect	+3.3 V	0.61 A	0.92 A
	+12 V	1.36 A	2.04 A
	Power	18.33 W	27.52 W
Optical	+3.3 V	1.12 A	1.68 A
	+12 V	1.36 A	2.04 A
	Power	20.02 W	30.02 W

Physical Characteristics

Dimensions	131 mm × 21 mm × 214 mm (5.16 in. × 0.83 in. × 8.43	3 in.)
------------	---	--------

		•	· · · · · · · · · · · · · · · · · · ·
Weight	275 g (9.70 oz)		
PXIe slots	One		



NOTE

For detailed dimensional drawings and 3D models, visit *ni.com/dimensions* and search for PXIe-8280.

Export Compliance

This product is subject to control under the U.S. Export Administration Regulations (15 CFR Part 730 et. seq.) administered by the U.S. Department of Commerce's Bureau of Industry and Security (BIS) (www.bis.doc.gov) and other applicable U.S. export control laws and sanctions regulations. This product may also be subject to additional license requirements of other countries' regulations.

Additionally, this product may also require export licensing before being returned to NI. The issuance of a Return Material Authorization (RMA) by NI does not constitute export authorization. The user must comply with all applicable export laws prior to exporting or re-exporting this product. See ni.com/legal/export-compliance for more information and to request relevant import classification codes (e.g. HTS), export classification codes (e.g. ECCN), and other import/export data.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the Engineering a Healthy Planet web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

EU and UK Customers

Waste Electrical and Electronic Equipment (WEEE) —At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/ environment/weee.

电子信息产品污染控制管理办法(中国 RoHS)

◎⑤◎ 中国 RoHS — NI 符合中国电子信息产品中限制使用某些有害物质指令(RoHS)。关 于 NI 中国 RoHS 合规性信息,请登录 ni.com/environment/rohs_chinα。(For information about China RoHS compliance, go to ni.com/environment/ rohs china.)

Product Certifications and Declarations

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit ni.com/ product-certifications, search by model number, and click the appropriate link.

NI Services

Visit *ni.com/support* to find support resources including documentation, downloads, and troubleshooting and application development self-help such as tutorials and examples.

Visit *ni.com/services* to learn about NI service offerings such as calibration options, repair, and replacement.

Visit *ni.com/register* to register your NI product. Product registration facilitates technical support and ensures that you receive important information updates from NI.

NI corporate headquarters is located at 11500 N Mopac Expwy, Austin, TX, 78759-3504, USA.

