

---

# USB-8506

# Specifications

---

2025-07-22



# Contents

USB-8506 Specifications ..... 3

# USB-8506 Specifications

## USB-8506 Specifications

This document lists specifications for the USB-8506 1-port and 2-port LIN interface device.

## Definitions

**Warranted** specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

**Characteristics** describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the performance met by a majority of models.
- **Nominal** specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are **Typical** unless otherwise noted.

## Conditions

Specifications are typical at 0 °C to 55 °C unless otherwise noted.

## USB-8506 Pinout

Use the pinout to connect to terminals on the USB-8506.

Figure 1. USB-8506 Connector Pinout




Table 1. Signal Descriptions

| D-SUB Pin | Signal | Description                                   |
|-----------|--------|-----------------------------------------------|
| 1         | NC     | No connection                                 |
| 2         | NC     | No connection                                 |
| 3         | COM    | LIN reference ground                          |
| 4         | NC     | No connection                                 |
| 5         | (SHLD) | Optional LIN shield                           |
| 6         | (COM)  | Optional LIN reference ground                 |
| 7         | LIN    | LIN data line                                 |
| 8         | NC     | No connection                                 |
| 9         | VSUP   | External power supply +8 V to +18 V) required |

## Bus Interface

|     |                    |
|-----|--------------------|
| USB | USB 2.0 High-Speed |
|-----|--------------------|

## Power Requirements

USB 2.0, bus-powered device

|                      |                                                                   |
|----------------------|-------------------------------------------------------------------|
| Input voltage        | 4.5 V min, 5.25 V max                                             |
| Working mode current | 500 mA maximum, 200 mA typical (2 ports), 180 mA typical (1 port) |
| USB suspend          | 2.5 mA maximum                                                    |

# Environmental

## Operating Environment

|                     |                                                 |
|---------------------|-------------------------------------------------|
| Ambient temperature | 0 °C to 55 °C                                   |
| Relative humidity   | 10% to 90%, noncondensing                       |
| Maximum altitude    | 2,000 m (800 mbar) at 25 °C ambient temperature |

Indoor use only.

## Storage Environment

|                     |                          |
|---------------------|--------------------------|
| Ambient temperature | -20 °C to 70 °C          |
| Relative humidity   | 5% to 95%, noncondensing |
| Pollution Degree    | 2                        |

## Physical

### Dimensions

|        |                                                               |
|--------|---------------------------------------------------------------|
| 1 port | 8.38 cm x 10.29 cm x 2.49 cm (3.30 in. x 4.05 in. x 0.98 in.) |
| 2 port | 9.27 cm x 10.29 cm x 2.49 cm (3.65 in. x 4.05 in. x 0.98 in.) |

## Weight

|        |                 |
|--------|-----------------|
| 1 port | 207 g (7.30 oz) |
| 2 port | 215 g (7.58 oz) |

## Cable Length

|                          |     |
|--------------------------|-----|
| Captive USB cable length | 2 m |
|--------------------------|-----|

## I/O Connectors

|                                    |                      |
|------------------------------------|----------------------|
| USB                                | Standard Type A plug |
| LIN Interface                      | 9-pin male D-SUB     |
| Sync Port (only on 2-port variant) | 3-pin Combicon       |

## LIN Characteristics

|                                                            |             |
|------------------------------------------------------------|-------------|
| Transceiver                                                | NXP TJA1028 |
| Max baud rate                                              | 20 kbps     |
| Battery voltage (VBAT) power requirement (always required) |             |

|                                                                        |                                           |
|------------------------------------------------------------------------|-------------------------------------------|
| Input Voltage                                                          | +8 VDC to +18 VDC                         |
| <b>Typical power consumption from VBAT (tested under VBAT = +12 V)</b> |                                           |
| Normal mode                                                            | 14 mA (with on board termination enabled) |
| Standby mode                                                           | 7 mA (with on board termination disabled) |
| Sleep mode                                                             | 290 $\mu$ A                               |

## Onboard Termination (If Enabled)

|         |              |
|---------|--------------|
| Typical | 1 k $\Omega$ |
|---------|--------------|

## Sync Port

|                                         |                                               |
|-----------------------------------------|-----------------------------------------------|
| I/O compatibility                       | 5V TTL compatible                             |
| Number of generic triggers <sup>1</sup> | 2                                             |
| Supported Input Time base frequencies   | 1 MHz, 10 MHz, and 20 MHz with auto detection |
| Supported Output Time base frequency    | 1 MHz                                         |

- Each generic trigger can be configured independently as input or output, clock or trigger. Refer to the ***NI-XNET Hardware and Software Help*** for details.

# Isolation

The USB-8506 offers port-to-port (2-port variant) and port-to-USB (both 1 port and 2 port) isolation.

## Isolation Voltage

| Port-to-earth ground |                                |
|----------------------|--------------------------------|
| Continuous           | 60 VDC, Measurement Category I |



**Note** The COM signals of LIN ports on USB-8506 are not connected to the USB ground. This isolation is intended to prevent ground loops and does not meet UL ratings for safety isolation.

## Maximum Voltage on LIN Ports

This voltage is the maximum voltage that can be applied or output without creating a safety hazard.

Connect only the voltages that are within these limits.

|             |                                                |
|-------------|------------------------------------------------|
| Port-to-COM | -40 VDC to +40 VDC max, Measurement Category I |
|-------------|------------------------------------------------|

Measurement Category I is for measurement performed on circuits not directly connected to the electrical distribution system referred to as MAINS voltage. MAINS is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics.



**Caution** Do not connect the USB-8506 to signals or use for measurements

within Measurement Categories II, III, or IV.



**Attention** Ne connectez pas le USB-8506 à des signaux et ne l'utilisez pas pour effectuer des mesures dans les catégories de mesure II, III ou IV.



**Note** Measurement Categories CAT I and CAT O (Other) are equivalent. These test and measurement circuits are not intended for direct connection to the MAINS building installations of Measurement Categories CAT II, CAT III, and CAT IV.

## Safety Compliance Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



**Note** For safety certifications, refer to the product label or the [Product Certifications and Declarations](#) section.

## Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



**Note** Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



**Note** In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia and New Zealand (per CISPR 11) Class A equipment is intended for use only in heavy-industrial locations.



**Notice** For EMC declarations and certifications, and additional information, refer to the [Product Certifications and Declarations](#) section.

## CE Compliance

This product meets the essential requirements of applicable European Directives, as follows:

- 2014/35/EU; Low-Voltage Directive (safety)
- 2014/30/EU; Electromagnetic Compatibility Directive (EMC)
- 2011/65/EU; Restriction of Hazardous Substances (RoHS)
- 2014/53/EU; Radio Equipment Directive (RED)
- 2014/34/EU; Potentially Explosive Atmospheres (ATEX)

## Product Certifications and Declarations

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit [ni.com/product-certifications](https://ni.com/product-certifications), search by model number, and click the appropriate link.

## Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Engineering a Healthy Planet*** web page at [ni.com/environment](https://ni.com/environment). This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

## EU and UK Customers

-  **Waste Electrical and Electronic Equipment (WEEE)**—At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit [ni.com/environment/weee](https://ni.com/environment/weee).

## 电子信息产品污染控制管理办法（中国RoHS）

-  **中国RoHS**—NI符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于NI中国RoHS合规性信息，请登录 [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china)。(For information about China RoHS compliance, go to [ni.com/environment/rohs\\_china](https://ni.com/environment/rohs_china).)